

Session Customizations

10/14/2019

Colleen Brown

HELP Facility

Remember where to get HELP

- HELP
- HELP by task
- HELP by commad
- HELP CP command
- HELP CMS command
- HELP XEDIT subcmds

Some interesting CP commands

- IGS has things set up so that CPPFKEY EXEC is called to set up common PFKeys.
 - IMMED option
 - SUBST option
- Some common things to set on PFKey's
 - RETRIEVE
 - RDRL
 - FILELIST
- SET
- QUERY

Some interesting CMS commands

- L – Listfile
- COPY – Copyfile
- PEEK – Peek
- BROWSE – Browse
- XEDIT – Xedit editor
- RECEIVE – Receive a file from your reader
- PEEK – Peek at a file in your reader
- SET – Set various things
- QUERY – Query various things
- VMLINK – Link and access a disk with a nickname

Some interesting XEDIT subcommands

- File – Save your file and exit
- Locate – Locate a word or string in your file
- Clocate - Locate a word or string in a column in your file
- Count - Count the number of occurrences of a string
- Power - Continuously type as if the screen is one, long line
- Save - Save your file changes but don't exit
- Split/Join vs SPLTJOIN – Split a line or join 2 lines

Slide 5

KM1

Replace Bill Norton

Kathryn Murtha, 1/22/2019

Some interesting XEDIT subcommands

- Set
 - Case Upper, lower, mixed
 - Color For specific areas of the screen
 - Curline Position of the current line on the screen
 - Filemode Change the file mode of the file
 - Filename Change the file name of the file
 - Filetype Change the file type of the file
 - Nulls Set trailing blanks to blanks or nulls
 - Num Set line number in the prefix area
 - PFn Set a PF key
 - Prefix Set the prefix area on
 - Scale Set a scale line on
 - SCREEN Divide the physical screen into n logical screens
 - Spill Specifies if data spills onto a new line
 - TABLINE Turn tabs on
 - TABS Set tab columns
 - VERIFY Controls the display of lines
 - WRAP Specifies if the editor is to “wrap around” when EOF is reached
 - ZONE Specifies the columns to be scanned for target searches

Slide 6

KM1

Replace Bill Norton

Kathryn Murtha, 1/22/2019

PROFILE EXEC

- CP SP PRT *
- SET RDYMSG SMSG
- CP SET RETRIEVE MAX
- CP SET LINEDIT ON
- CP LINK DATABASE 233 233 RR
- ACCESS 233 U/U
- SYNONYM MYSIN
- CP SET PF9 IMMEDIATE FILEL
- CP SET PF12 RETRIEVE
- CP SET RETRIEVE MAX
- CP SCREEN STA RED
- CP SCREEN INA PINK
- CP SCREEN OUTA YELLOW

Slide 7

KM1

Replace Bill Norton

Kathryn Murtha, 1/22/2019

PROFILE XEDIT

- TRACE OFF
- ARG FN FT FM
- SET ARB ON \$
- SET CASE M I
- SET CURLINE ON 11
- SET IMAGE ON
- SET NUMBER ON
- SET PREFIX ON LEFT
- SET SCALE ON 4
- SET WRAP ON
- SET NULLS OFF
- SET PF2 SPLIT CURSOR
- SET PF3 JOIN CURSOR
- SET PF4 UP
- SET PF5 SCHANGE 6
- SET COLOR PENDING YELLOW
- SET COLOR PREFIX BLUE REV
- SET COLOR TABLINE PINK
-

Slide 8

KM1

Replace Bill Norton

Kathryn Murtha, 1/22/2019

PROFILE XEDIT cont.

- MACRO XEDITPF
- SET COLOR MSGLINE BLUE REV
- SET COLOR SCALE WHITE
- SET COLOR ARROW BLUE REV
- SET COLOR IDLINE YELLOW REV
- SET COLOR CURLINE TUR REV
- SET COLOR STATAREA YELLOW REV
- SET COLOR FILEAREA WHITE REV
- SET COLOR TOF TUR
- IF FT = ASSEMBLE then SET TRUNC 72
- IF FT = ASSEMBLE then SET SERIAL ALL 10000 10000
- IF FT = MACRO then SET TRUNC 72
- IF FT = MACRO then SET SERIAL ALL 10000 10000

Slide 9

KM1

Replace Bill Norton

Kathryn Murtha, 1/22/2019

XEDITPF XEDIT

- * XEDIT PF KEYS FOR GENERAL TYPE OF EDITING....
- SET PF1 ?
- SET PF2 SPLIT CURSOR
- SET PF3 JOIN CURSOR
- SET PF4 UP
- SET PF5 SCHANG 6
- SET PF6
- SET PF7 BACKWARD
- SET PF8 FORWARD
- SET PF9
- *ET PF10 TABKEY 1 10 16 30 40 50 60 72
- SET PF11 CURSOR COLUMN
- SET RESERV 3 HIGH 1=? 2=SPLT 3=JOIN 4=U 5=SCHANGE 6= 7=B 8=F 9= 10=TAB
11=CUR-LINE 12=S&D

Slide 10

KM1

Replace Bill Norton

Kathryn Murtha, 1/22/2019

PROFPEEK XEDIT

```

• /*****
• /*
• /* Copyright -
• /*
• /* THIS MODULE IS "RESTRICTED MATERIALS OF IBM"
• /* 5654-A17 (C) COPYRIGHT IBM CORP. - 1982, 2001
• /* LICENSED MATERIALS - PROPERTY OF IBM
• /* ALL RIGHTS RESERVED.
• /*
• /* Status - z/VM Version 3, Release 1.0
• /*****
• address 'XEDIT'
•
• rcode = 0 /* initialize the return code to zero */
•
• 'COMMAND CASE M I' /* CASE MIXED IGNORE */
• if rc ->= 0 then do
•   rcode = rc
•   call EXIT
• end

```

Slide 11

KM1

Replace Bill Norton

Kathryn Murtha, 1/22/2019

CMS Default Set

- **DEFAULTS** List the defaults you have set
- **DEFAULTS SET** Set new defaults

